

30W Flameproof LED Emergency Linear Fixture - 220V AC - ATEX/IECEX [ATEX-HALP-EMG-24-2L-LED-1X30W-R1-220V](#)



ATEX-HALP-EMG-24-2L-LED-1X30W-R1-220V Flameproof Emergency LED Light

Listing: International, European Union

Lamp Technology: LED

Dimensions: -

Lamp Quantity: 1

Weight: -

Voltage: 220V AC

Frequency: 50/60 Hz

Total Watts: 30W

Total Lumens: 2,480 lms

Luminous Efficacy: 100 lm/W

Lamp Life: 50,000+ Hours

Color Temperature: 5700K

Color Rendering Index: >75

Lamp Type: -

Lamp Base: -

Replacement Lamp: -

Beam Angle: -

Lighting Configuration: Flood Pattern

Power Efficiency: -

Power Factor: >0.95

Emergency Runtime: 90 Minutes

Emergency Lumens: 2,480 lms (1 Lamp)

Battery Recharge Time: 24 Hrs

Emergency Status Display: (3) LEDs (Red, Yellow, Green)

Amperage: 0.25A @ 120V, 0.125A @ 240V

Ambient Operating Temp Range: -25°C to +50°C/+55°C

Operating Temp Rating: T6

Housing Material: Glass Fiber Reinforced Polyester

Housing Finish: -

Lens Material: UV Resistant Polycarbonate

Gasket Material: Foam

Mount: -

Terminals: (2) L1, L2, L, N, PE - 0.39" (10mm)

Hub Quantity: 1

Hub Size/Location: (1) 1.5" (M25) @ Side

Stopping Plugs: (2) 1.5" (M25) Molded Plastic/Polyamide

Ratings/Approvals

ATEX/IECEX Rated

Zone 1/Zone 2

Zone 21/Zone 22

Ex db eb mb op is q IIC T6/T5 Gb

Ex tb IIC T80°C/T85°C Db

IP66

Emergency Backup Mode

Special Orders- Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: +01-903-498-3364

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Links (Click on the below items to view):

- [large](#)
- [medium](#)
- [SpecSheet](#)
- [HigResPic1](#)